



OTC 19072

State of the Art in Float-Overs

Michel Seij and Henk de Groot, Dockwise Shipping

Copyright 2007, Offshore Technology Conference

This paper was prepared for presentation at the 2007 Offshore Technology Conference held in Houston, Texas, U.S.A., 30 April–3 May 2007.

This paper was selected for presentation by an OTC Program Committee following review of information contained in an abstract submitted by the author(s). Contents of the paper, as presented, have not been reviewed by the Offshore Technology Conference and are subject to correction by the author(s). The material, as presented, does not necessarily reflect any position of the Offshore Technology Conference, its officers, or members. Papers presented at OTC are subject to publication review by Sponsor Society Committees of the Offshore Technology Conference. Electronic reproduction, distribution, or storage of any part of this paper for commercial purposes without the written consent of the Offshore Technology Conference is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of where and by whom the paper was presented. Write Librarian, OTC, P.O. Box 833836, Richardson, TX 75083-3836, U.S.A., fax 01-972-952-9435.

Abstract

The float-over deck installation is in use as an effective installation method since the eighties. The method has developed and the applicability has widened to heavier integrated decks and harsher environments such as West-Africa and West-Australia.

The paper describes the state of the art in float-over deck installations by an overview of a number of typical float-over operations. Each of these float-overs has a typicality related to:

- o Integrated deck weight;
- o Environment;
- o Installation concept.

The present state of the art has been reviewed in a SWOT analysis from a contractor's and operator's perspective. Strength, weaknesses, opportunities and threats have been summarized to identify a way forward for future developments.

Possibilities for the way forward to achieve the following objectives have been outlined in the paper:

- o Improved workability;
- o Reduced jacket slot requirements;
- o Standardization to reduce early commitment requirements.

Introduction

Installing an integrated deck onto a jacket structure is an operation that has been executed by using semi submersible crane vessels and derrick barges already for many years.

Offshore integration costs can be reduced since the integrated deck weight can be over above the capacity of (locally) available crane capacity.

The float-over deck installation is proving to be a competitive alternative for such an offshore installation operation.

In recent years the concept of float-over deck installation has matured. With the help of a lengthening track record and benefits over lift operations, the float-over deck installation is taken into account as a reliable means of installing the assets.

Since the float-over deck installation has been used only for a limited number of projects compared to the lifting operations performed by semi submersible crane vessel, improvements to the concept are still to be expected.

Float-over Deck Installation: Sequence

For better understanding of the advantages and dis-advantages of the float-over deck installation over semi submersible crane vessels, a brief introduction to the float-over concept is presented.

Load-Out

The load-out is the starting point of a float-over deck installation. The integrated deck will be build on-shore and needs to be loaded out onto the installation vessel.

Load-outs can be performed either by self propelled modular trailers or by the use of skid tracks.

Figure 1 presents a skidded load-out of a 15.000 tons module onto self propelled installation vessel Blue Marlin.



Figure 1: Skidded load-out of 15.000 tons module

Requirements for the load-out stage are governed by the following parameters: